



EverPro GLOVES

Coated Work Gloves Manufacture Since 2011

13 Gauge HPPE Liner With
Latex Crinkle Coated Cut
Resistant Work Glove (Cut 301)

SPECIFICATION

PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide the glove cut level to 5, suitable to most of the high cut risk conditions.

Latex coating with good function of anti-slip and high elasticity.

For cut resistant glove the abrasion and tear performance all can arrive level 4

APPLICATIONS

√ Construction √ Furniture manufacturing

√ Glass Process √ Automobile subassembly

√ Car and ship Manufacture √ Intricate assembly

√ Light sheet metal assembly

FEATURES

Color: Grey/blue

Liner Material: Cut 5 HPPE

Coating Material: Latex

Finishing: Crinkle palm

Package: 12pairs/bag, 120pairs/carton

Printing: ink/silk/heat transfer

ADVANTAGES

√ Cut level 5

√ High flexible performance

√ Anti-slip and good grip

√ Good abrasion performance and long lifetime

√ Soft and elastic cuff



EN388 MECHANICAL RISKS



Charater	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance(number of cycles)	100	500	2000	8000	-
Blade cut resistance(index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture reisitance	20	60	100	150	-
Cut resistance method (EN ISO 13997)	A to F				