



# EverPro GLOVES

Coated Work Gloves Manufacture Since 2011

13 Gauge HPPE Liner With  
Latex Sandy Coated Cut  
Resistant Work Glove(Cut 401)

## SPECIFICATION

### PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide

the glove cut level to 5, suitable to most of the high cut risk conditions.

Latex sandy coating with good function of anti-slip and workable in both wet and dry condition.

For cut resistant glove the abrasion and tear performance all can arrive level 4.

### APPLICATIONS

√ Construction    √ Furniture manufacturing

√ Glass Process    √ Automobile subassembly

√ Car and ship Manufacture    √ Intricate assembly

√ Light sheet metal assembly

### FEATURES

Color: Grey/black

Liner Material: Cut 5 HPPE

Coating Material: Latex

Finishing: Sandy

Package: 12pairs/bag, 120pairs/carton

Printing: ink/silk/heat transfer

### ADVANTAGES

√ Cut level 5

√ High flexible performance


√ Anti-slip and good grip

√ Good abrasion performance and long lifetime

√ Suitable in both wet and dry conditions



### EN388 MECHANICAL RISKS



Charater	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance(number of cycles)	100	500	2000	8000	-
Blade cut resistance(index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture reistance	20	60	100	150	-
Cut resistance method (EN ISO 13997)	A to F				