



EverPro
GLOVES
Coated Work Gloves Manufacture Since 2011

**15 Gauge HPPE Liner With
Nitrile Foam Thumb Coated Cut
Resistant Work Glove (Cut 801)**

SPECIFICATION

PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide the glove cut level to 5, suitable to most of the high cut risk conditions.

Nitrile foam coating can be oil-resistant and water-resistant. and high breathability performance. Thumb coated supply more protection to hands.

For cut resistant glove the abrasion and tear performance all can arrive level 4.

APPLICATIONS

- ✓ Construction
- ✓ Furniture manufacturing
- ✓ Glass Process
- ✓ Automobile subassembly
- ✓ Car and ship Manufacture
- ✓ Intricate assembly
- ✓ Light sheet metal assembly

FEATURES


- Color: Blue/black
- Liner Material: Cut 5 HPPE
- Coating Material: Nitrile
- Finishing: Foam palm and thumb
- Package: 12pairs/bag, 120pairs/carton
- Printing: ink/silk/heat transfer

ADVANTAGES

- ✓ Cut level 5
- ✓ High flexible performance
- ✓ Thinner and soft feeling
- ✓ Keep good grip both the wet and dry work conditions
- ✓ Good breathability



EN388 MECHANICAL RISKS



| Charater | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 |
|--|---------|---------|---------|---------|---------|
| Abraision resistance(number of cycles) | 100 | 500 | 2000 | 8000 | - |
| Blade cut resistance(index) | 1.2 | 2.5 | 5 | 10 | 20 |
| Tear resistance (N) | 10 | 25 | 50 | 75 | - |
| Puncture reisitance | 20 | 60 | 100 | 150 | - |
| Cut resistance method (EN ISO 13997) | A to F | | | | |