



# EverPro GLOVES

Coated Work Gloves Manufacture Since 2011

13 Gauge HPPE Liner With  
Nitrile Fully And Sandy Palm Cut  
Resistant Work Glove (Cut 901)

## SPECIFICATION

### PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide the glove cut level to 5, suitable to most of the high cut risk conditions.

Nitrile fully coating can be oil-resistant and water-resistant and fully protection.

Sandy Nitrile can be workable both in wet and dry work conditions.

For cut resistant glove the abrasion and tear performance all can arrive level 4.

### APPLICATIONS

- ✓ Construction
- ✓ Furniture manufacturing
- ✓ Glass Process
- ✓ Automobile subassembly
- ✓ Car and ship Manufacture
- ✓ Intricate assembly
- ✓ Light sheet metal assembly

### FEATURES


- Color: Blue/black
- Liner Material: Cut 5 HPPE
- Coating Material: Nitrile
- Finishing: fully and sandy palm
- Package: 12pairs/bag, 120pairs/carton
- Printing: ink/silk/heat transfer

### ADVANTAGES

- ✓ Cut level 5
- ✓ Fully protection
- ✓ Keep good grip both the wet and dry work conditions
- ✓ Oil-resistant and water-resistant



### EN388 MECHANICAL RISKS



Character	Level 1	Level 2	Level 3	Level 4	Level 5
Abrasion resistance(number of cycles)	100	500	2000	8000	-
Blade cut resistance(index)	1.2	2.5	5	10	20
Tear resistance (N)	10	25	50	75	-
Puncture resistance	20	60	100	150	-
Cut resistance method (EN ISO 13997)	A to F				