



EverPro GLOVES

Coated Work Gloves Manufacture Since 2011

13 Gauge HPPE Liner With
Nitrile Foam Palm Cut Resistant
Work Glove (Cut 1001)

SPECIFICATION

PRODUCT DESCRIPTION

Liner HPPE combined with PE silk, Nylon, Acrylic, Fiberglass which provide the glove cut level to 5, suitable to most of the high cut risk conditions.

Nitrile foam coating can be oil-resistant and water-resistant. Also can supply the good breathability and soft touch feeling.

For cut resistant glove the abrasion and tear performance all can arrive level 4.

APPLICATIONS

- ✓ Construction
- ✓ Furniture manufacturing
- ✓ Glass Process
- ✓ Automobile subassembly
- ✓ Car and ship Manufacture
- ✓ Intricate assembly
- ✓ Light sheet metal assembly

FEATURES


- Color: Blue/black
- Liner Material: Cut 5 HPPE
- Coating Material: Nitrile
- Finishing: foam palm
- Package: 12pairs/bag, 120pairs/carton
- Printing: ink/silk/heat transfer

ADVANTAGES

- ✓ Cut level 5
- ✓ Soft touch feeling
- ✓ Good breathability
- ✓ Oil-resistant and water-resistant



EN388 MECHANICAL RISKS



| Charater | Level 1 | Level 2 | Level 3 | Level 4 | Level 5 |
|--|---------|---------|---------|---------|---------|
| Abraision resistance(number of cycles) | 100 | 500 | 2000 | 8000 | - |
| Blade cut resistance(index) | 1.2 | 2.5 | 5 | 10 | 20 |
| Tear resistance (N) | 10 | 25 | 50 | 75 | - |
| Puncture reisitance | 20 | 60 | 100 | 150 | - |
| Cut resistance method (EN ISO 13997) | A to F | | | | |